## **Center for Tobacco Reference Products**

Telephone: (859) 257-2660 Fax: (859) 257-6012 Email: ctrp@uky.edu 1401 University Drive Lexington, KY 40546-0236 www.ctrp.uky.edu

# Certificate of Analysis Certified Reference Moist Snuff

Certificate Number: 2023-01-3S3-CTRP

Certification Date: 3/31/2023

Validity: This document is valid until 3/31/2028 unless superseded by a new CoA at an earlier date.

Superseded CoA: 2019-01\_CTRP

Description of CRM

Moist Snuff

Lot/Batch Number

**STRP 353** 

Matrix

Tobacco blend

Major starting materials

Dark fired tobacco, air-cured tobacco, burley tobacco stem, sodium carbonate, sodium chloride, water

Reference Moist Snuff Certified Values and Uncertainties

| Parameter      | Certified Value   | Certified<br>Uncertainty<br>(U <sub>CRM</sub> ) | Coverage Factor<br>of<br>U <sub>CRM</sub> | Unit     | Number of<br>accepted<br>data points |
|----------------|---|---|---|----------|--------------------------------------|
| Total Nicotine | 11.450  | 0.660   | 2.95                                      | mg/g     | 132                                  |
| Free Nicotine  | 3.147   | 0.589   | 2.56                                      | mg/g     | 132                                  |
| NNK            | 0.539   | 0.056   | 2.98                                      | μg/g     | 132                                  |
| NNN            | 1.859   | 0.229   | 3.08                                      | μg/g     | 132                                  |
| NAT            | 2.360   | 0.366   | 3.10                                      | μg/g     | 132                                  |
| NAB            | 0.165   | 0.018   | 2.95                                      | μg/g     | 132                                  |
| Acetaldehyde   | 1.75  | 0.77  | 2.05                                      | μg/g     | 132                                  |
| Crotonaldehyde | <loq< td=""><td>NA</td><td>NA</td><td>μg/g</td><td>NA</td></loq<> | NA  | NA  | μg/g     | NA                                   |
| Formaldehyde   | 0.91  | 0.36  | 2.96                                      | μg/g     | 132                                  |
| Benzo[a]pyrene | 79.59   | 13.87   | 2.96                                      | ng/g     | 132                                  |
| Cadmium        | 487   | 109   | 2.31                                      | ng/g     | 132                                  |
| Arsenic        | 76.8  | 25.0  | 2.67                                      | ng/g     | 132                                  |
| Moisture       | 54.8  | 0.2   | 2.01                                      | %        | 132                                  |
| pH .           | 7.60  | 0.10  | 2.46                                      | pH units | 132                                  |

CAM HT BS

#### CERTIFIED VALUES AND UNCERTAINTIES:

The "Certified Values" listed above are unweighted means of results submitted by four ISO 17025-accredited laboratories using a combination of methods and instrumentation that emulate actual methods and instrumentation techniques currently utilized in the analysis of each parameter in the analytical community. No assumptions were made regarding the accuracy or precision of each laboratory therefore no weighting is done on the results of each lab.

The "Certified Uncertainty",  $U_{CRM}$ , listed above are expanded uncertainties intended to provide approximately 95% confidence interval around the respective reference values obtained by multiplying the combined standard uncertainty with a coverage factor k, equal to the t-value based on the approximated degrees of freedom using the Welch-Satterthwaite equation. Each "Certified Uncertainty" includes an uncertainty component that accounts for systematic error among the methods used by different laboratories.

Values reported as <LOQ have concentrations reported as below the level of quantification by the ISO 17025 contract labs that analyzed the samples.

The Certified Values and Uncertainties for the analytical parameters contained herein are on an "as received" basis.

#### STATEMENT OF TRACEABILITY:

The traceability of the reference values and uncertainties certified herein are maintained through an unbroken chain of comparisons to appropriate standards with suitable procedures and measurement uncertainties by virtue of the ISO 17025 – accreditations possessed by the four participating laboratories. The accredited analytical methods used by participating laboratories are listed below.

#### LIST OF METHODS USED:

Analytes in smokeless tobacco

| Carbonyls                             | LP-743/AM-240/TWT-00355          |  |  |
|---------------------------------------|----------------------------------|--|--|
| Nicotine                              | LP-411/ENT182/AM-072/T-301       |  |  |
| Moisture                              | LP-801.1/ENT046/AM-071/TWT-00324 |  |  |
| pH                                    | LP-031/ENT058/AM-071/T-310       |  |  |
| Metals                                | LP-416/AM-052/T-306              |  |  |
| Benzo[α]pyrene                        | LP-711/ENT212/AM-125/TWT-00357   |  |  |
| Tobacco Specific Nitrosamines (TSNAs) | LP-412.1/ENT210/AM031/TWT-00333  |  |  |

INTENDED USE: This product may be used for analytical method development, assigning values to materials (when applicable), and, equipment calibration to any applicable extent.

INSTRUCTIONS FOR CORRECT USE: This reference material should be stored in sealed containers or bags at -20°C until testing. Prior to analysis, the reference materials should be unopened and transferred to a refrigerator for a minimum of 24 hours or until they are completely thawed, and then moved to room temperature for at least 2 hours until it reaches temperature equilibrium. Once the reference materials are equilibrated to room temperature, the reference materials may be stored at 4°C for up to one week, if they will not be analyzed immediately. Any reference materials found to have damaged package should be discarded.

### HAZARD INFORMATION: N/A

HOMOGENEITY: Homogeneity of this material is reflected as an uncertainty component of "Certified Uncertainty" as indicated in this Certificate of Analysis.

NAMES AND SIGNATURES OF CERTIFYING OFFICERS:

Certificate Approved by:

Ling Yuan, Pr. D. Director, CTRP Certificate Approved by:

Orlando D. Chambers, Ph.D. Principal Investigator

Certificate Approved by:

Huihua Ji, MS

Analytical Lab Director/ Deputy Quality Control Certificate Approved by:

C. Ruth McNees, Ph.D.

Quality Control/Quality Assurance

Certificate Approved by:

Brent J. Shelton, Ph.D. Statistical design and data processing

Certificate Approved by:

Stacey Slone, MS Statistical design and data processing